

## **Accident prevention regulations inspection by qualified technician with registered certificate**

After a fall or decommissioning, the device must be subjected to a detailed accident prevention regulations inspection by an authorised qualified technician.

At intervals set by the operating company, but at least every 12 months, the device shall be subjected to a detailed accident prevention regulations inspection by an authorised qualified technician.

The accident prevention regulations inspection is carried out according to the manufacturer's specifications. The safety instructions of the maintenance manual must be observed.

Only original manufacturer parts are permitted for replacing components.

Damaged or corroded fall indicator components must be replaced by new original parts from the manufacturer.

Repairing components of this module is strictly prohibited.

## Accident prevention regulations checklist for devices type Falpro V1

OK = in order

Rep. = repair

n/a = not applicable

### 1 Inspection Logbook

- 1.1 Is it available?
- 1.2 Are all entries complete?
- 1.3 Access possible at any time?

OK	Rep.	n/a

### 2 Operation Manual

- 2.1 Is it available?
- 2.2 Access possible at any time?

OK	Rep.	n/a

### 3 Base plate

- 3.1 Welds No cracks
- 3.2 Anti-slip segments Secure / undamaged / complete
- 3.3 4x load attachment point Undamaged / secure

OK	Rep.	n/a
X		
X		
X		

### 4 Swivel head

- 4.1 Pivot bearing Smooth / free of play
- 4.2 Pivot bearing seal Secure / undamaged
- 4.3 Turn lock Smooth / functional / straight/ easily rotatable
- 4.4 Swivel head bolts Straight / parallel to the plate
- 4.5 Welds No cracks

OK	Rep.	n/a
X		
X		
X		
X		
X		

### 5 Safety unit

- 5.1 Welds No cracks
- 5.2 Spring No breaks / corrosion free
- 5.3 Spring holder No cracks / aligned / secure
- 5.4 Bearing Free to move / lubricated
- 5.5 Bolt Aligned / straight

OK	Rep.	n/a
X		
X		
X		
X		
X		

### 6 Hydraulics

- 6.1 Pump No oil loss / leaks
- 6.2 Pump mechanics Secure / undamaged / free to move / lubricated
- 6.3 Oil level Check / no leaks
- 6.4 Hoses Check (exchange every 6 years)

OK	Rep.	n/a
X		
X		
X		
checked		

### 7 Base mast

- 7.1 Welds No cracks
- 7.2 Bearing Free to move / lubricated
- 7.3 Bolt Aligned / straight

OK	Rep.	n/a
X		
X		
X		

### 8 Push rod

- 8.1 Welds No cracks
- 8.2 Bearing Free to move / lubricated
- 8.3 Bolt Aligned / straight

OK	Rep.	n/a
X		
X		
X		

### 9 Extension Arm

- 9.1 Welds No cracks
- 9.2 Bearing Free to move / lubricated
- 9.3 Bolt Aligned / straight
- 9.4 Fall indicator Disassemble / renew corrosion protection

OK	Rep.	n/a
X		
X		
X		
X		

### 10 Fall indicator removed

- 10.1 Condition No damage / corrosion free
- 10.2 Release cable Smooth / corrosion free (exchange every 4 years)
- 10.3 Safety wire Corrosion free / undamaged (exchange every 4 years)
- 10.4 Assembly Renew lubrication / set release force

OK	Rep.	n/a
X		
X		
X		
renew		

### 11 Labelling and documentation

- 11.1 Warnings Complete / readable / undamaged

OK	Rep.	n/a
X		

### 12 Tests and Settings

- 12.1 Anchor point height 7.4 - 7.8 ft. / 2250 - 2350 mm
- 12.2 Response time configuration change Max. 2.0 sec
- 12.3 Release force Under 264 lbs / 120 kg
- 12.4 Functional test At least 3x

OK	Rep.	n/a
7.6 / 2320		
1,8		
220 / 100		
4		

Note:

The Accident Prevention Regulations period of validity until \_\_\_\_\_ has been marked on the device and the implemented inspection details have been  documented  not documented in the logbook.

Technician Name:	Place:	Signature:
Technician Number:	Date:	

## Accident prevention regulations checklist for devices type Falpro V1

OK = in order

Rep. = repair

n/a = not applicable

### 1 Inspection Logbook

- 1.1 Is it available?
- 1.2 Are all entries complete?
- 1.3 Access possible at any time?

OK	Rep.	n/a

### 2 Operation Manual

- 2.1 Is it available?
- 2.2 Access possible at any time?

OK	Rep.	n/a

### 3 Base plate

- 3.1 Welds No cracks
- 3.2 Anti-slip segments Secure / undamaged / complete
- 3.3 4x load attachment Undamaged / secure

OK	Rep.	n/a

### 4 Swivel head

- 4.1 Pivot bearing Smooth / free of play
- 4.2 Pivot bearing seal Secure / undamaged
- 4.3 Turn lock Smooth / functional / straight/ easily rotatable
- 4.4 Swivel head bolts Straight / parallel to the plate
- 4.5 Welds No cracks

OK	Rep.	n/a

### 5 Safety unit

- 5.1 Welds No cracks
- 5.2 Spring No breaks / corrosion free
- 5.3 Spring holder No cracks / aligned / secure
- 5.4 Bearing Free to move / lubricated
- 5.5 Bolt Aligned / straight

OK	Rep.	n/a

### 6 Hydraulics

- 6.1 Pump No oil loss / leaks
- 6.2 Pump mechanics Secure / undamaged / free to move / lubricated
- 6.3 Oil level Check / no leaks
- 6.4 Hoses Check (exchange every 6 years)

OK	Rep.	n/a

### 7 Base mast

- 7.1 Welds No cracks
- 7.2 Bearing Free to move / lubricated
- 7.3 Bolt Aligned / straight

OK	Rep.	n/a

### 8 Push rod

- 8.1 Welds No cracks
- 8.2 Bearing Free to move / lubricated
- 8.3 Bolt Aligned / straight

OK	Rep.	n/a

### 9 Extension Arm

- 9.1 Welds No cracks
- 9.2 Bearing Free to move / lubricated
- 9.3 Bolt Aligned / straight
- 9.4 Fall indicator Disassemble / renew corrosion protection

OK	Rep.	n/a

### 10 Fall indicator removed

- 10.1 Condition No damage / corrosion free
- 10.2 Release cable Smooth / corrosion free (exchange every 4 years)
- 10.3 Safety wire Corrosion free / undamaged (exchange every 4 years)
- 10.4 Assembly Renew lubrication / set release force

OK	Rep.	n/a

### 11 Labelling and documentation

- 11.1 Warnings Complete / readable / undamaged

OK	Rep.	n/a

### 12 Tests and Settings

- 12.1 Anchor point height 7.4 - 7.8 ft. / 2250 - 2350 mm
- 12.2 Response time configuration change Max. 2.0 sec
- 12.3 Release force Under 264 lbs / 120 kg
- 12.4 Functional test At least 3x

OK	Rep.	n/a

Note:

The Accident Prevention Regulations period of validity until \_\_\_\_\_ has been marked on the device and the implemented inspection details have been  documented  not documented in the logbook.

Technician Name:	Place:	Signature:
Technician Number:	Date:	

## Accident prevention regulations checklist for devices type Falpro V1

OK = in order

Rep. = repair

n/a = not applicable

### 1 Inspection Logbook

- 1.1 Is it available?
- 1.2 Are all entries complete?
- 1.3 Access possible at any time?

OK	Rep.	n/a

### 2 Operation Manual

- 2.1 Is it available?
- 2.2 Access possible at any time?

OK	Rep.	n/a

### 3 Base plate

- 3.1 Welds No cracks
- 3.2 Anti-slip segments Secure / undamaged / complete
- 3.3 4x load attachment Undamaged / secure

OK	Rep.	n/a

### 4 Swivel head

- 4.1 Pivot bearing Smooth / free of play
- 4.2 Pivot bearing seal Secure / undamaged
- 4.3 Turn lock Smooth / functional / straight/ easily rotatable
- 4.4 Swivel head bolts Straight / parallel to the plate
- 4.5 Welds No cracks

OK	Rep.	n/a

### 5 Safety unit

- 5.1 Welds No cracks
- 5.2 Spring No breaks / corrosion free
- 5.3 Spring holder No cracks / aligned / secure
- 5.4 Bearing Free to move / lubricated
- 5.5 Bolt Aligned / straight

OK	Rep.	n/a

### 6 Hydraulics

- 6.1 Pump No oil loss / leaks
- 6.2 Pump mechanics Secure / undamaged / free to move / lubricated
- 6.3 Oil level Check / no leaks
- 6.4 Hoses Check (exchange every 6 years)

OK	Rep.	n/a

### 7 Base mast

- 7.1 Welds No cracks
- 7.2 Bearing Free to move / lubricated
- 7.3 Bolt Aligned / straight

OK	Rep.	n/a

### 8 Push rod

- 8.1 Welds No cracks
- 8.2 Bearing Free to move / lubricated
- 8.3 Bolt Aligned / straight

OK	Rep.	n/a

### 9 Extension Arm

- 9.1 Welds No cracks
- 9.2 Bearing Free to move / lubricated
- 9.3 Bolt Aligned / straight
- 9.4 Fall indicator Disassemble / renew corrosion protection

OK	Rep.	n/a

### 10 Fall indicator removed

- 10.1 Condition No damage / corrosion free
- 10.2 Release cable Smooth / corrosion free (exchange every 4 years)
- 10.3 Safety wire Corrosion free / undamaged (exchange every 4 years)
- 10.4 Assembly Renew lubrication / set release force

OK	Rep.	n/a

### 11 Labelling and documentation

- 11.1 Warnings Complete / readable / undamaged

OK	Rep.	n/a

### 12 Tests and Settings

- 12.1 Anchor point height 7.4 - 7.8 ft. / 2250 - 2350 mm
- 12.2 Response time configuration change Max. 2.0 sec
- 12.3 Release force Under 264 lbs / 120 kg
- 12.4 Functional test At least 3x

OK	Rep.	n/a

Note:

The Accident Prevention Regulations period of validity until \_\_\_\_\_ has been marked on the device and the implemented inspection details have been  documented  not documented in the logbook.

Technician Name:	Place:	Signature:
Technician Number:	Date:	

## Accident prevention regulations checklist for devices type Falpro V1

OK = in order

Rep. = repair

n/a = not applicable

### 1 Inspection Logbook

- 1.1 Is it available?
- 1.2 Are all entries complete?
- 1.3 Access possible at any time?

OK	Rep.	n/a

### 2 Operation Manual

- 2.1 Is it available?
- 2.2 Access possible at any time?

OK	Rep.	n/a

### 3 Base plate

- 3.1 Welds No cracks
- 3.2 Anti-slip segments Secure / undamaged / complete
- 3.3 4x load attachment Undamaged / secure

OK	Rep.	n/a

### 4 Swivel head

- 4.1 Pivot bearing Smooth / free of play
- 4.2 Pivot bearing seal Secure / undamaged
- 4.3 Turn lock Smooth / functional / straight/ easily rotatable
- 4.4 Swivel head bolts Straight / parallel to the plate
- 4.5 Welds No cracks

OK	Rep.	n/a

### 5 Safety unit

- 5.1 Welds No cracks
- 5.2 Spring No breaks / corrosion free
- 5.3 Spring holder No cracks / aligned / secure
- 5.4 Bearing Free to move / lubricated
- 5.5 Bolt Aligned / straight

OK	Rep.	n/a

### 6 Hydraulics

- 6.1 Pump No oil loss / leaks
- 6.2 Pump mechanics Secure / undamaged / free to move / lubricated
- 6.3 Oil level Check / no leaks
- 6.4 Hoses Check (exchange every 6 years)

OK	Rep.	n/a

### 7 Base mast

- 7.1 Welds No cracks
- 7.2 Bearing Free to move / lubricated
- 7.3 Bolt Aligned / straight

OK	Rep.	n/a

### 8 Push rod

- 8.1 Welds No cracks
- 8.2 Bearing Free to move / lubricated
- 8.3 Bolt Aligned / straight

OK	Rep.	n/a

### 9 Extension Arm

- 9.1 Welds No cracks
- 9.2 Bearing Free to move / lubricated
- 9.3 Bolt Aligned / straight
- 9.4 Fall indicator Disassemble / renew corrosion protection

OK	Rep.	n/a

### 10 Fall indicator removed

- 10.1 Condition No damage / corrosion free
- 10.2 Release cable Smooth / corrosion free (exchange every 4 years)
- 10.3 Safety wire Corrosion free / undamaged (exchange every 4 years)
- 10.4 Assembly Renew lubrication / set release force

OK	Rep.	n/a

### 11 Labelling and documentation

- 11.1 Warnings Complete / readable / undamaged

OK	Rep.	n/a

### 12 Tests and Settings

- 12.1 Anchor point height 7.4 - 7.8 ft. / 2250 - 2350 mm
- 12.2 Response time configuration change Max. 2.0 sec
- 12.3 Release force Under 264 lbs / 120 kg
- 12.4 Functional test At least 3x

OK	Rep.	n/a

Note:

The Accident Prevention Regulations period of validity until \_\_\_\_\_ has been marked on the device and the implemented inspection details have been  documented  not documented in the logbook.

Technician Name:	Place:	Signature:
Technician Number:	Date:	

## Accident prevention regulations checklist for devices type Falpro V1

OK = in order

Rep. = repair

n/a = not applicable

### 1 Inspection Logbook

- 1.1 Is it available?
- 1.2 Are all entries complete?
- 1.3 Access possible at any time?

OK	Rep.	n/a

### 2 Operation Manual

- 2.1 Is it available?
- 2.2 Access possible at any time?

OK	Rep.	n/a

### 3 Base plate

- 3.1 Welds No cracks
- 3.2 Anti-slip segments Secure / undamaged / complete
- 3.3 4x load attachment Undamaged / secure

OK	Rep.	n/a

### 4 Swivel head

- 4.1 Pivot bearing Smooth / free of play
- 4.2 Pivot bearing seal Secure / undamaged
- 4.3 Turn lock Smooth / functional / straight/ easily rotatable
- 4.4 Swivel head bolts Straight / parallel to the plate
- 4.5 Welds No cracks

OK	Rep.	n/a

### 5 Safety unit

- 5.1 Welds No cracks
- 5.2 Spring No breaks / corrosion free
- 5.3 Spring holder No cracks / aligned / secure
- 5.4 Bearing Free to move / lubricated
- 5.5 Bolt Aligned / straight

OK	Rep.	n/a

### 6 Hydraulics

- 6.1 Pump No oil loss / leaks
- 6.2 Pump mechanics Secure / undamaged / free to move / lubricated
- 6.3 Oil level Check / no leaks
- 6.4 Hoses Check (exchange every 6 years)

OK	Rep.	n/a

### 7 Base mast

- 7.1 Welds No cracks
- 7.2 Bearing Free to move / lubricated
- 7.3 Bolt Aligned / straight

OK	Rep.	n/a

### 8 Push rod

- 8.1 Welds No cracks
- 8.2 Bearing Free to move / lubricated
- 8.3 Bolt Aligned / straight

OK	Rep.	n/a

### 9 Extension Arm

- 9.1 Welds No cracks
- 9.2 Bearing Free to move / lubricated
- 9.3 Bolt Aligned / straight
- 9.4 Fall indicator Disassemble / renew corrosion protection

OK	Rep.	n/a

### 10 Fall indicator removed

- 10.1 Condition No damage / corrosion free
- 10.2 Release cable Smooth / corrosion free (exchange every 4 years)
- 10.3 Safety wire Corrosion free / undamaged (exchange every 4 years)
- 10.4 Assembly Renew lubrication / set release force

OK	Rep.	n/a

### 11 Labelling and documentation

- 11.1 Warnings Complete / readable / undamaged

OK	Rep.	n/a

### 12 Tests and Settings

- 12.1 Anchor point height 7.4 - 7.8 ft. / 2250 - 2350 mm
- 12.2 Response time configuration change Max. 2.0 sec
- 12.3 Release force Under 264 lbs / 120 kg
- 12.4 Functional test At least 3x

OK	Rep.	n/a

Note:

The Accident Prevention Regulations period of validity until \_\_\_\_\_ has been marked on the device and the implemented inspection details have been  documented  not documented in the logbook.

Technician Name:	Place:	Signature:
Technician Number:	Date:	

## Accident prevention regulations checklist for devices type Falpro V1

OK = in order

Rep. = repair

n/a = not applicable

### 1 Inspection Logbook

- 1.1 Is it available?
- 1.2 Are all entries complete?
- 1.3 Access possible at any time?

OK	Rep.	n/a

### 2 Operation Manual

- 2.1 Is it available?
- 2.2 Access possible at any time?

OK	Rep.	n/a

### 3 Base plate

- 3.1 Welds No cracks
- 3.2 Anti-slip segments Secure / undamaged / complete
- 3.3 4x load attachment Undamaged / secure

OK	Rep.	n/a

### 4 Swivel head

- 4.1 Pivot bearing Smooth / free of play
- 4.2 Pivot bearing seal Secure / undamaged
- 4.3 Turn lock Smooth / functional / straight/ easily rotatable
- 4.4 Swivel head bolts Straight / parallel to the plate
- 4.5 Welds No cracks

OK	Rep.	n/a

### 5 Safety unit

- 5.1 Welds No cracks
- 5.2 Spring No breaks / corrosion free
- 5.3 Spring holder No cracks / aligned / secure
- 5.4 Bearing Free to move / lubricated
- 5.5 Bolt Aligned / straight

OK	Rep.	n/a

### 6 Hydraulics

- 6.1 Pump No oil loss / leaks
- 6.2 Pump mechanics Secure / undamaged / free to move / lubricated
- 6.3 Oil level Check / no leaks
- 6.4 Hoses Check (exchange every 6 years)

OK	Rep.	n/a

### 7 Base mast

- 7.1 Welds No cracks
- 7.2 Bearing Free to move / lubricated
- 7.3 Bolt Aligned / straight

OK	Rep.	n/a

### 8 Push rod

- 8.1 Welds No cracks
- 8.2 Bearing Free to move / lubricated
- 8.3 Bolt Aligned / straight

OK	Rep.	n/a

### 9 Extension Arm

- 9.1 Welds No cracks
- 9.2 Bearing Free to move / lubricated
- 9.3 Bolt Aligned / straight
- 9.4 Fall indicator Disassemble / renew corrosion protection

OK	Rep.	n/a

### 10 Fall indicator removed

- 10.1 Condition No damage / corrosion free
- 10.2 Release cable Smooth / corrosion free (exchange every 4 years)
- 10.3 Safety wire Corrosion free / undamaged (exchange every 4 years)
- 10.4 Assembly Renew lubrication / set release force

OK	Rep.	n/a

### 11 Labelling and documentation

- 11.1 Warnings Complete / readable / undamaged

OK	Rep.	n/a

### 12 Tests and Settings

- 12.1 Anchor point height 7.4 - 7.8 ft. / 2250 - 2350 mm
- 12.2 Response time configuration change Max. 2.0 sec
- 12.3 Release force Under 264 lbs / 120 kg
- 12.4 Functional test At least 3x

OK	Rep.	n/a

Note:

The Accident Prevention Regulations period of validity until \_\_\_\_\_ has been marked on the device and the implemented inspection details have been  documented  not documented in the logbook.

Technician Name:	Place:	Signature:
Technician Number:	Date:	

## Accident prevention regulations checklist for devices type Falpro V1

OK = in order

Rep. = repair

n/a = not applicable

### 1 Inspection Logbook

- 1.1 Is it available?
- 1.2 Are all entries complete?
- 1.3 Access possible at any time?

OK	Rep.	n/a

### 2 Operation Manual

- 2.1 Is it available?
- 2.2 Access possible at any time?

OK	Rep.	n/a

### 3 Base plate

- 3.1 Welds No cracks
- 3.2 Anti-slip segments Secure / undamaged / complete
- 3.3 4x load attachment Undamaged / secure

OK	Rep.	n/a

### 4 Swivel head

- 4.1 Pivot bearing Smooth / free of play
- 4.2 Pivot bearing seal Secure / undamaged
- 4.3 Turn lock Smooth / functional / straight/ easily rotatable
- 4.4 Swivel head bolts Straight / parallel to the plate
- 4.5 Welds No cracks

OK	Rep.	n/a

### 5 Safety unit

- 5.1 Welds No cracks
- 5.2 Spring No breaks / corrosion free
- 5.3 Spring holder No cracks / aligned / secure
- 5.4 Bearing Free to move / lubricated
- 5.5 Bolt Aligned / straight

OK	Rep.	n/a

### 6 Hydraulics

- 6.1 Pump No oil loss / leaks
- 6.2 Pump mechanics Secure / undamaged / free to move / lubricated
- 6.3 Oil level Check / no leaks
- 6.4 Hoses Check (exchange every 6 years)

OK	Rep.	n/a

### 7 Base mast

- 7.1 Welds No cracks
- 7.2 Bearing Free to move / lubricated
- 7.3 Bolt Aligned / straight

OK	Rep.	n/a

### 8 Push rod

- 8.1 Welds No cracks
- 8.2 Bearing Free to move / lubricated
- 8.3 Bolt Aligned / straight

OK	Rep.	n/a

### 9 Extension Arm

- 9.1 Welds No cracks
- 9.2 Bearing Free to move / lubricated
- 9.3 Bolt Aligned / straight
- 9.4 Fall indicator Disassemble / renew corrosion protection

OK	Rep.	n/a

### 10 Fall indicator removed

- 10.1 Condition No damage / corrosion free
- 10.2 Release cable Smooth / corrosion free (exchange every 4 years)
- 10.3 Safety wire Corrosion free / undamaged (exchange every 4 years)
- 10.4 Assembly Renew lubrication / set release force

OK	Rep.	n/a

### 11 Labelling and documentation

- 11.1 Warnings Complete / readable / undamaged

OK	Rep.	n/a

### 12 Tests and Settings

- 12.1 Anchor point height 7.4 - 7.8 ft. / 2250 - 2350 mm
- 12.2 Response time configuration change Max. 2.0 sec
- 12.3 Release force Under 264 lbs / 120 kg
- 12.4 Functional test At least 3x

OK	Rep.	n/a

Note:

The Accident Prevention Regulations period of validity until \_\_\_\_\_ has been marked on the device and the implemented inspection details have been  documented  not documented in the logbook.

Technician Name:	Place:	Signature:
Technician Number:	Date:	

## Accident prevention regulations checklist for devices type Falpro V1

OK = in order

Rep. = repair

n/a = not applicable

### 1 Inspection Logbook

- 1.1 Is it available?
- 1.2 Are all entries complete?
- 1.3 Access possible at any time?

OK	Rep.	n/a

### 2 Operation Manual

- 2.1 Is it available?
- 2.2 Access possible at any time?

OK	Rep.	n/a

### 3 Base plate

- 3.1 Welds No cracks
- 3.2 Anti-slip segments Secure / undamaged / complete
- 3.3 4x load attachment Undamaged / secure

OK	Rep.	n/a

### 4 Swivel head

- 4.1 Pivot bearing Smooth / free of play
- 4.2 Pivot bearing seal Secure / undamaged
- 4.3 Turn lock Smooth / functional / straight/ easily rotatable
- 4.4 Swivel head bolts Straight / parallel to the plate
- 4.5 Welds No cracks

OK	Rep.	n/a

### 5 Safety unit

- 5.1 Welds No cracks
- 5.2 Spring No breaks / corrosion free
- 5.3 Spring holder No cracks / aligned / secure
- 5.4 Bearing Free to move / lubricated
- 5.5 Bolt Aligned / straight

OK	Rep.	n/a

### 6 Hydraulics

- 6.1 Pump No oil loss / leaks
- 6.2 Pump mechanics Secure / undamaged / free to move / lubricated
- 6.3 Oil level Check / no leaks
- 6.4 Hoses Check (exchange every 6 years)

OK	Rep.	n/a

### 7 Base mast

- 7.1 Welds No cracks
- 7.2 Bearing Free to move / lubricated
- 7.3 Bolt Aligned / straight

OK	Rep.	n/a

### 8 Push rod

- 8.1 Welds No cracks
- 8.2 Bearing Free to move / lubricated
- 8.3 Bolt Aligned / straight

OK	Rep.	n/a

### 9 Extension Arm

- 9.1 Welds No cracks
- 9.2 Bearing Free to move / lubricated
- 9.3 Bolt Aligned / straight
- 9.4 Fall indicator Disassemble / renew corrosion protection

OK	Rep.	n/a

### 10 Fall indicator removed

- 10.1 Condition No damage / corrosion free
- 10.2 Release cable Smooth / corrosion free (exchange every 4 years)
- 10.3 Safety wire Corrosion free / undamaged (exchange every 4 years)
- 10.4 Assembly Renew lubrication / set release force

OK	Rep.	n/a

### 11 Labelling and documentation

- 11.1 Warnings Complete / readable / undamaged

OK	Rep.	n/a

### 12 Tests and Settings

- 12.1 Anchor point height 7.4 - 7.8 ft. / 2250 - 2350 mm
- 12.2 Response time configuration change Max. 2.0 sec
- 12.3 Release force Under 264 lbs / 120 kg
- 12.4 Functional test At least 3x

OK	Rep.	n/a

Note:

The Accident Prevention Regulations period of validity until \_\_\_\_\_ has been marked on the device and the implemented inspection details have been  documented  not documented in the logbook.

Technician Name:	Place:	Signature:
Technician Number:	Date:	

## Accident prevention regulations checklist for devices type Falpro V1

OK = in order

Rep. = repair

n/a = not applicable

### 1 Inspection Logbook

- 1.1 Is it available?
- 1.2 Are all entries complete?
- 1.3 Access possible at any time?

OK	Rep.	n/a

### 2 Operation Manual

- 2.1 Is it available?
- 2.2 Access possible at any time?

OK	Rep.	n/a

### 3 Base plate

- 3.1 Welds No cracks
- 3.2 Anti-slip segments Secure / undamaged / complete
- 3.3 4x load attachment Undamaged / secure

OK	Rep.	n/a

### 4 Swivel head

- 4.1 Pivot bearing Smooth / free of play
- 4.2 Pivot bearing seal Secure / undamaged
- 4.3 Turn lock Smooth / functional / straight/ easily rotatable
- 4.4 Swivel head bolts Straight / parallel to the plate
- 4.5 Welds No cracks

OK	Rep.	n/a

### 5 Safety unit

- 5.1 Welds No cracks
- 5.2 Spring No breaks / corrosion free
- 5.3 Spring holder No cracks / aligned / secure
- 5.4 Bearing Free to move / lubricated
- 5.5 Bolt Aligned / straight

OK	Rep.	n/a

### 6 Hydraulics

- 6.1 Pump No oil loss / leaks
- 6.2 Pump mechanics Secure / undamaged / free to move / lubricated
- 6.3 Oil level Check / no leaks
- 6.4 Hoses Check (exchange every 6 years)

OK	Rep.	n/a

### 7 Base mast

- 7.1 Welds No cracks
- 7.2 Bearing Free to move / lubricated
- 7.3 Bolt Aligned / straight

OK	Rep.	n/a

### 8 Push rod

- 8.1 Welds No cracks
- 8.2 Bearing Free to move / lubricated
- 8.3 Bolt Aligned / straight

OK	Rep.	n/a

### 9 Extension Arm

- 9.1 Welds No cracks
- 9.2 Bearing Free to move / lubricated
- 9.3 Bolt Aligned / straight
- 9.4 Fall indicator Disassemble / renew corrosion protection

OK	Rep.	n/a

### 10 Fall indicator removed

- 10.1 Condition No damage / corrosion free
- 10.2 Release cable Smooth / corrosion free (exchange every 4 years)
- 10.3 Safety wire Corrosion free / undamaged (exchange every 4 years)
- 10.4 Assembly Renew lubrication / set release force

OK	Rep.	n/a

### 11 Labelling and documentation

- 11.1 Warnings Complete / readable / undamaged

OK	Rep.	n/a

### 12 Tests and Settings

- 12.1 Anchor point height 7.4 - 7.8 ft. / 2250 - 2350 mm
- 12.2 Response time configuration change Max. 2.0 sec
- 12.3 Release force Under 264 lbs / 120 kg
- 12.4 Functional test At least 3x

OK	Rep.	n/a

Note:

The Accident Prevention Regulations period of validity until \_\_\_\_\_ has been marked on the device and the implemented inspection details have been  documented  not documented in the logbook.

Technician Name:	Place:	Signature:
Technician Number:	Date:	

## Accident prevention regulations checklist for devices type Falpro V1

OK = in order

Rep. = repair

n/a = not applicable

### 1 Inspection Logbook

- 1.1 Is it available?
- 1.2 Are all entries complete?
- 1.3 Access possible at any time?

OK	Rep.	n/a

### 2 Operation Manual

- 2.1 Is it available?
- 2.2 Access possible at any time?

OK	Rep.	n/a

### 3 Base plate

- 3.1 Welds No cracks
- 3.2 Anti-slip segments Secure / undamaged / complete
- 3.3 4x load attachment Undamaged / secure

OK	Rep.	n/a

### 4 Swivel head

- 4.1 Pivot bearing Smooth / free of play
- 4.2 Pivot bearing seal Secure / undamaged
- 4.3 Turn lock Smooth / functional / straight/ easily rotatable
- 4.4 Swivel head bolts Straight / parallel to the plate
- 4.5 Welds No cracks

OK	Rep.	n/a

### 5 Safety unit

- 5.1 Welds No cracks
- 5.2 Spring No breaks / corrosion free
- 5.3 Spring holder No cracks / aligned / secure
- 5.4 Bearing Free to move / lubricated
- 5.5 Bolt Aligned / straight

OK	Rep.	n/a

### 6 Hydraulics

- 6.1 Pump No oil loss / leaks
- 6.2 Pump mechanics Secure / undamaged / free to move / lubricated
- 6.3 Oil level Check / no leaks
- 6.4 Hoses Check (exchange every 6 years)

OK	Rep.	n/a

### 7 Base mast

- 7.1 Welds No cracks
- 7.2 Bearing Free to move / lubricated
- 7.3 Bolt Aligned / straight

OK	Rep.	n/a

### 8 Push rod

- 8.1 Welds No cracks
- 8.2 Bearing Free to move / lubricated
- 8.3 Bolt Aligned / straight

OK	Rep.	n/a

### 9 Extension Arm

- 9.1 Welds No cracks
- 9.2 Bearing Free to move / lubricated
- 9.3 Bolt Aligned / straight
- 9.4 Fall indicator Disassemble / renew corrosion protection

OK	Rep.	n/a

### 10 Fall indicator removed

- 10.1 Condition No damage / corrosion free
- 10.2 Release cable Smooth / corrosion free (exchange every 4 years)
- 10.3 Safety wire Corrosion free / undamaged (exchange every 4 years)
- 10.4 Assembly Renew lubrication / set release force

OK	Rep.	n/a

### 11 Labelling and documentation

- 11.1 Warnings Complete / readable / undamaged

OK	Rep.	n/a

### 12 Tests and Settings

- 12.1 Anchor point height 7.4 - 7.8 ft. / 2250 - 2350 mm
- 12.2 Response time configuration change Max. 2.0 sec
- 12.3 Release force Under 264 lbs / 120 kg
- 12.4 Functional test At least 3x

OK	Rep.	n/a

Note:

The Accident Prevention Regulations period of validity until \_\_\_\_\_ has been marked on the device and the implemented inspection details have been  documented  not documented in the logbook.

Technician Name:	Place:	Signature:
Technician Number:	Date:	

## Accident prevention regulations checklist for devices type Falpro V1

OK = in order

Rep. = repair

n/a = not applicable

### 1 Inspection Logbook

- 1.1 Is it available?
- 1.2 Are all entries complete?
- 1.3 Access possible at any time?

OK	Rep.	n/a

### 2 Operation Manual

- 2.1 Is it available?
- 2.2 Access possible at any time?

OK	Rep.	n/a

### 3 Base plate

- 3.1 Welds No cracks
- 3.2 Anti-slip segments Secure / undamaged / complete
- 3.3 4x load attachment Undamaged / secure

OK	Rep.	n/a

### 4 Swivel head

- 4.1 Pivot bearing Smooth / free of play
- 4.2 Pivot bearing seal Secure / undamaged
- 4.3 Turn lock Smooth / functional / straight/ easily rotatable
- 4.4 Swivel head bolts Straight / parallel to the plate
- 4.5 Welds No cracks

OK	Rep.	n/a

### 5 Safety unit

- 5.1 Welds No cracks
- 5.2 Spring No breaks / corrosion free
- 5.3 Spring holder No cracks / aligned / secure
- 5.4 Bearing Free to move / lubricated
- 5.5 Bolt Aligned / straight

OK	Rep.	n/a

### 6 Hydraulics

- 6.1 Pump No oil loss / leaks
- 6.2 Pump mechanics Secure / undamaged / free to move / lubricated
- 6.3 Oil level Check / no leaks
- 6.4 Hoses Check (exchange every 6 years)

OK	Rep.	n/a

### 7 Base mast

- 7.1 Welds No cracks
- 7.2 Bearing Free to move / lubricated
- 7.3 Bolt Aligned / straight

OK	Rep.	n/a

### 8 Push rod

- 8.1 Welds No cracks
- 8.2 Bearing Free to move / lubricated
- 8.3 Bolt Aligned / straight

OK	Rep.	n/a

### 9 Extension Arm

- 9.1 Welds No cracks
- 9.2 Bearing Free to move / lubricated
- 9.3 Bolt Aligned / straight
- 9.4 Fall indicator Disassemble / renew corrosion protection

OK	Rep.	n/a

### 10 Fall indicator removed

- 10.1 Condition No damage / corrosion free
- 10.2 Release cable Smooth / corrosion free (exchange every 4 years)
- 10.3 Safety wire Corrosion free / undamaged (exchange every 4 years)
- 10.4 Assembly Renew lubrication / set release force

OK	Rep.	n/a

### 11 Labelling and documentation

- 11.1 Warnings Complete / readable / undamaged

OK	Rep.	n/a

### 12 Tests and Settings

- 12.1 Anchor point height 7.4 - 7.8 ft. / 2250 - 2350 mm
- 12.2 Response time configuration change Max. 2.0 sec
- 12.3 Release force Under 264 lbs / 120 kg
- 12.4 Functional test At least 3x

OK	Rep.	n/a

Note:

The Accident Prevention Regulations period of validity until \_\_\_\_\_ has been marked on the device and the implemented inspection details have been  documented  not documented in the logbook.

Technician Name:	Place:	Signature:
Technician Number:	Date:	